# **PAN RACKS**

## **UNIVERSAL PAN RACKS**

# KELMAX by





ITEM #	MODEL #	QTY:
PROJECT:		
OPTIONS: TYES	□NO	

### **Standard Features & Benefits**

- Universal pan racks are multipurpose racks designed to transport 18" x 26" and 12" x 20" pans, with 18 3/8" opening
- Units designed to hold trays and pans from the bottom
- Can be used for roll-in boxes
- Units are all welded aluminum
- Runners are welded to 1 1/4" tubing
- ◆ All units have 5" polyurethane plate casters
- 64 3/4" high units can be used for roll-in boxes
- ◆ Rack covers available
- Lifetime guarantee against rust

#### 6 3/8" Runner

	Tray	Spacing	D x L x H		Weight	
Model No.	Capacity	(in.)	(in.)	(mm.)	(lbs.)	(kg.)
Runners for Oval T	rays, Sheet	Pans, and	Steam Table Pans			
4H1312	10	6	27 1/2 x 25 1/2 x 72 1/2	699 x 648 x 1842	70	32
4H1318	12	5	27 1/2 x 25 1/2 x 72 1/2	699 x 648 x 1842	78	35
4H1317	11	5	27 1/2 x 25 1/2 x 65	699 x 648 x 1651	80	36
4H1325	20	6	49 x 27 x 72	1245 x 686 x 1829	160	73
4H4914	20	6	49 x 27 x 72	1245 x 686 x 1829	160	73

STORAGE PRODUCTS GROUP

# **PAN RACKS**

## **SPECIFICATIONS**

#### 3 1/4" Runner

	Tray	Spacing	DxLxH		Weight	
Model No.	Capacity	(in.)	(in.)	(mm.)	(lbs.)	(kg.)
Universal Pan Rac	:ks					
4H1238	12	5	27 x 21 x 69	685 x 533 x 1753	52	23
4H1231	11	5	27 x 21 x 64 1/2	685 x 533 x 1638	53	24
4H1252	18	3	27 x 21 x 64 1/2	685 x 533 x 1638	68	31
4H1264	20	3	27 x 21 x 69	685 x 533 x 1753	72	33
For Roll-In Refrige	For Roll-In Refrigerators 65" Clear					
4H1227	10	6	27 x 24 x 69	685 x 610 x 1753	57	26
4H1243	12	5	27 x 24 x 69	685 x 610 x 1753	59	27
4H1262	18	3	27 x 24 x 64 1/2	685 x 610 x 1638	71	32
4H2453	20	3	27 x 24 x 69	685 x 610 x 1753	75	34

#### **Unit Options**

Model No.	Description
/PC	5" Polyurethane Plate Casters
/BK	Locking Brakes
/VB	Vertical Corner Bumpers (4)
/SB	Solid Base
/SBCB	Solid Base Continuous Bumper
/TG	Aluminum Tray Guards

To select an option, please contact factory for part number.

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke



# **PAN RACKS**


#### **SPECIFICATIONS**

#### **CONSTRUCTION:**

Constructed of Heavy Duty extruded Type 6063 aluminum alloy. All uprights and runners are fully welded.

#### **UPRIGHTS & CROSS-BRACES:**

Sides/Uprights consist of 1 1/4" square aluminum tubing (.109" thick) continuously welded. Reinforced gussets at bottom.



#### **RUNNERS:**

All runners are fully welded to the uprights. Runners are 1 1/4" x 6 1/4" or 1 1/4" x 3 1/8"

#### CASTERS:

Units feature a plate caster with a polyurethane 5" x 1 1/2" wheel, with full swivel. 4H1325 and 4H4914 has 5" by 2" polyurethane plate casters. 20 7/8 -18 3/8 23 1/24 DPENING DPENING SPACING-SPACING TYP×18 TYP×10 64 1/8 11 7/8" 71 3/16 FALL-THRU 10 3/4″ FALL THRU 4H1312

AMCO • Freestyle • ISS • Kelmax • LPI • Universal Stainless • Gillis-Jarke

SPG International, LLC 11230 Harland Drive NE Covington, GA 30014 877-503-4SPG (4774)

The best names in the business all have one thing in common.



4H1252