T39 Bristol Ridge®









Bristol Ridge[®] features a lighter-weight double rib high/ low design that performs the scraping function of the mat. The ribbed surface brushes, channels, and conceals dirt and debris and is the perfect choice for light to medium traffic areas.

Test	Test Description	*Results	
ASTM D3884-01	Abrasion Resistance	-1.15 grams (4.4%)	
ASTM D6540-00	Accelerated Soiling	Based on Visual Inspection 4.0 - Vacuum Rating 4.5 - Rating After Extraction	
ASTM D5252-98a	Accelerated Wear	Based on visual inspection @ 4,000 cycles Noticeable change in appearance and color	
CPSC FF 1-70 (ASTM D-2859)	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass	
-	Water Retention	Weight Gain = 27.4% (0.25 gals./yd ²)	
****	arformed by an independent testing laboratory	11/2014	

*All testing of NoTrax $\ensuremath{^\circ}$ floor matting has been performed by an independent testing laboratory.

11/2014

Appearance Rating Key				
5	No change			
4	Slight change			
3	Noticeable change			
2	Considerable change			
1	Severe change			





T39: Quality Met

QUALITY METER	FAIR	GOOD	BETTER	BEST	SUPERIOR
water absorption					
dirt scraping					
outdoor use	NR				
wearability					,

- 19 oz. face weight
- Thickness: 3/8"
- Solution dyed to prevent fading
- Vinyl backing to reduce mat movement
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 3' x 20', 4' x 6', 4' x 8', 4' x 20'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 3', 4', and 6' widths (up to 60')