

Unit Specifications



Temperature Range

60° F - 120° F
(15° C - 49° C)



Water Removal Rate

10 lbs/ hr
(4.5 kg/hr)



Power Options (V / Φ / Hz)

208-220/240/1/50,
208-220/240/1/60

Learn more about
The CDS 10



CDS 10

Our Smallest Drying System

The CDS-10 is capable of removing up to 10 lbs of water per hour. Available in a 4 or 8 rack chamber option, this system can dry for flower or extraction. The smaller four rack chamber is perfect for extraction and capable of drying up to 220 lbs (100 kg) of material, while the eight rack chamber doubles the capacity to 440 lbs (200 kg) of flower per batch.

Features

- » Precise control over Temp, RH, & Laminar Airflow ensuring a gentle, even dry
- » Remote Cloud-Based Controls
- » Setpoint data logging for analyses
- » Terpene Capture
- » Washable Food-Grade Interior & Airflow Components
- » GMP/CE Safety Compliant



Distributed By: **OMEGA**
EQUIPMENT & SUPPLY



CHAMBER OPTIONS

4 Rack Chamber

8 Rack Chamber

| | | |
|-------------------------------------|---|--|
| Loading Space (L x W x H): | 4' 4" X 5' 2" X 6' 0" (1.32 M X 1.57 M X 1.83 M) | 7' 8" X 5' 2" X 6' 0" (2.34 M X 1.57 M X 1.83 M) |
| Total Footprint (L x W x H): | 11' 4" X 5' 8" X 9' 2" (3.46 M X 1.73 M X 2.79 M) | 16' 0" X 5' 8" X 9' 2" (4.88 M X 1.73 M X 2.79 M) |
| Drying Temp | 60° F (15° C) - Drying for Flower 90° F (32° C) - Drying for Extraction | 60° F (15° C) - Drying for Flower 90° F (32° C) - Drying for Extraction |
| Product Capacity | Wet: 200 - 220 lbs (91 - 100 kg) Dry: 50 - 55 lbs (23 - 25 kg) | Wet: 400 - 440 lbs (182 - 200 kg) Dry: 100 - 110 lbs (46 - 50 kg) |
| Interior Finish | Stainless / PVC (Food Grade) | Stainless / PVC (Food Grade) |
| Exterior Finish | Painted Galvanized | Painted Galvanized |



Distributed By: **OMEGA**
EQUIPMENT & SUPPLY