



## Unit Specifications



### Temperature Range

60° F - 120° F  
(15° C - 49° C)



### Water Removal Rate

60 lbs/ hr  
(27 kg/hr)



### Power Options ( V / $\Phi$ / Hz )

208-220/240/3/60,  
380/3/50, 480/3/60,  
575/3/60

Learn more about  
The CDS 60



## CDS 60

## Perfect for Mid-sized Grows

The CDS-60 can remove up to 60 lbs of water per hour and is available in an 18 or 36 rack configuration. Perfect for extraction, the 18 rack chamber can dry up to 990 lbs (450 kg), while the large 36 rack chamber dries up to 1980 lbs (900 kg) of wet flower per batch.

## Features

- » Precise control over Temp, RH, & Laminar Airflow ensuring a gentle, even dry
- » Remote Cloud-Based Controls
- » Setpoint data logging for analyses
- » Terpene Capture
- » Washable Food-Grade Interior & Airflow Components
- » GMP/CE Safety Compliant



Distributed By: **OMEGA**  
EQUIPMENT & SUPPLY



# CHAMBER OPTIONS

## 18 Rack Chamber

## 36 Rack Chamber

<b>Loading Space (L x W x H):</b>	11' 4" X 7' 7" X 6' 0" (3.46M X 2.31M X 1.83M)	23' 6" X 7' 6" X 5' 10" (7.16M X 2.29M X 1.78M)
<b>Total Footprint (L x W x H):</b>	21' 6" X 8' 0" X 9' 2" (6.55M X 2.44M X 2.79M)	33' 4" X 8' 0" X 9' 2" (11.16M X 2.44M X 2.79M)
<b>Drying Temp</b>	60° F (15° C) - Drying for Flower 90° F (32° C) - Drying for Extraction	60° F (15° C) - Drying for Flower 90° F (32° C) - Drying for Extraction
<b>Product Capacity</b>	Wet: 900 - 990 lbs (408 - 450 kg)  Dry: 225 - 247.5 lbs (102 - 112 kg)	Wet: 1,800 - 1,980 lbs (816 - 900 kg)  Dry: 450 - 495 lbs (204 - 224 kg)
<b>Interior Finish</b>	Stainless / PVC (Food Grade)	Stainless / PVC (Food Grade)
<b>Exterior Finish</b>	Painted Galvanized	Painted Galvanized

