





CRYSTAL PRODUCTION SYSTEM

Model: CPS-150

GET IN BUSINESS FASTER!



McGrane Lab Systems has partnered with Cascade Sciences to develop the CPS-150 System that is ideal for large volume crystallization. The system includes a jacketed reactor tank with precision temperature control, a cold trap, an air compressor to aide in transferring material, and two mixing tanks for continuous processing and efficient flow.



- Runs 25-30kg distillate in a single 12 hour run with up to 86% efficiency
- Approved for use with:
 - Pentane in C1D1 environment
 - Hexane, heptane in C1D2 environment
- Crystallization capability
 - Capable of crystallizing CBD or CBG
 - Runs as low as 70% potency distillate
- Patent pending Crystal Breaker
 - Allows for easy crystal removal
- Crystals can be dried in unit
 - Positions quickly and easily
- Closed loop operation
- Peer Reviewed / State Certifications
- NRTL Certified Mechanical Components

REQUIRED CONSUMABLES

- Isopropyl Alcohol
- Pentane, Heptane, or Hexane
- CBD or CBG Distillate







CRYSTAL REACTOR 150L Jacketed Reactor **Mobile Casters**

MIXING TANKS (2) 304 Stainless Steel

AIR COMPRESSOR California Air Tools 60040CAD

HUBER TEMP CONTROL CC-508 with Pilot ONE On Mobile Cart

-105°C COLD TRAP **CASCADE MAXTRAP 105** On Mobile Cart

ACCESSORIES All Thermal Fluids, Connection **Tubing & Installation Included**

503-847-9047 info@cascadesciences.com cascadesciences.com

6725 NE Evergreen Pkwy, Ste 106 Hillsboro, OR 97124





TEMP CONTROL - HUBER CC-508



-105°C COLD TRAP - MAXTRAP105



AIR COMPRESSOR 60040CAD

503-847-9047

info@cascadesciences.com cascadesciences.com

6725 NE Evergreen Pkwy, Ste 106 Hillsboro, OR 97124

CPS-150 System

SPECIFICATIONS

150L CRYSTAL REACTOR	Gen 2	Gen 3
Max Pressure	1 Bar	2 each 150L Vessels
Capacity	5.68 Gallon Jacketed Reactor	
Dimensions	32"L x 32"W x 30"H 32"L x 32"W x 65"H (with Crystal Breaker)	
Construction Material	304 Stainless Steel	
Mobile, On Casters		
MIXING TANK		
Tank	50L	37.5 Gal Brite Tank
Max Pressure	1 Bar	
Dimensions	24"L x 24"W x 35"H	
Construction Material	304 Stainless Steel	
Stirring	Manual	Electronic
TEMPERATURE CONTROL -	HUBER CC-508 OR EQUIVALENT	
Temperature Range	-55°C to 200°C	
Temperature Stability	±0.02°C	
Controller	Pilot ONE for Ramping	
Heating Capacity	2.45kW	
Bath Volume	5L	
Power Supply	208V / 1ph / 16.5AMP Includes cord/plug UL 6-20 20AMP Plug	
-105°C COLD TRAP - CASCA	DE SCIENCES MAXTRAP105	
Capacity	3Qt. (2839mL)	
Adapter	KF25 Inlet & Outlet	
Gasket	Viton	
Power Supply	115V / 1ph / 13AMP Includes cord/plug	
CFC / HCFC Free Refrigerar	nts	
AIR COMPRESSOR - CALIFO	ORNIA AIR TOOLS 60040CAD	
Power Supply	220V / 1ph / 14AMP Includes cord/plug (No 208V)	

AIR COMPRESSOR - CALIFORNIA AIR TOOLS 60040CAD		
Power Supply	220V / 1ph / 14AMP Includes cord/plug (No 208V)	
Dimensions	26"L x 26"W x 67"H	