	Project Name:			AIA#:
Model #:		_ Location:		
	Itam	#•	Quantity:	



Countertop Induction Range

Most energy efficient cooking in the world!

No open flames, portable and light weight. Ideal for omelet stations, catering, and more...









*Ferromagnetic Cookware Required

Suitable pans: steel or cast iron, enameled cast iron, stainless steel and aluminum if marked "suitable for induction cooking", flat-bottom pans/pots with diameter of 12 to 26 cm or 4.75" to 10"

Model

☐ IR1800

Standard Features

- 1800W, 120V
- 6 power levels
- Auto pan detection, allows range to detect if proper cookware/pan* is placed on cooktop
- Auto empty pan safety shut-off when timer runs to "0"
- 6 temperature settings from 150°F-450°F
- Over-heat protection for pan and electrical components, shuts unit off
- Touch pad controls with bright easy-to-read 4 digit LED display
- Digital timer with repeat time selection, from zero to 170 minutes
- Error code alert display
- Attached 5½-foot power cord and NEMA 5-15P plug
- Durable ceramic cooktop with stainless steel framing
- Low profile, 3" H
- Easy-to-clean flat surface control panel
- Durable molded plastic bottom

Warranty

One year parts and labor To select options see back

Approved by:	Date:



For Indoor Use Only

SPECIFICAT	SPECIFICATIONS CONTROL OF THE PROPERTY OF THE						
Model	Power Levels	Temp Settings	Cooking Surface	Electric	AMPs	Wattage	NEMA Plug Type
IR1800	6	150°F-450°F	4.75" to 9.5"	120V/60Hz	15	1800 W	5-15P (U.S.) 😲

DIMENS	DIMENSIONS & SHIPPING INFORMATION Carton reinforced for shipping. The weight and dimensions of reinforced carton are listed below and may vary from shipment to shipment.					
Carton reinf						
Model	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight		
IR1800	14" L × 12.25" W × 3" H (35.56 cm × 31.12 cm × 7.62 cm)	7.8 lbs. (3.54 kg)	17.75" L × 14.75" W× 5" H (45.1 cm × 37.46 cm × 12.7 cm)	9 lbs. (4.1 kg)		

STANDARD EQUIPMENT:

Auto pan detection: Range detects if proper cookware/pan is placed on cooktop.

Automatic shut-off: Automatically shuts off when timer runs to "0".

Over-heat protection: Unit senses when the pan overheats and when the electrical components overheat; the unit then shuts off.

Digital timer: Set timer from 0-170 minutes.

Bright LED display: Bright 4 digit LED display for easy viewing.

Suitable Pans:

Steel or cast iron, enameled cast iron, stainless steel and aluminum if marked "suitable for induction cooking", flat-bottom pans/pots with diameter of 12 to 26 cm or 4.75" to 10.25".

IMPORTANT: PERSONS WITH PACEMAKERS

Persons with pacemakers should stay at least 3 feet away from the induction range.

6-23-2017

When using the induction range with the general public, a pacemaker notice should be posted near the induction range.