SO-LOW Environmental Equipment Co., Inc.
10310 Spartan Dr., Cincinnati, Ohio 45215 USA
(513) 772-9410 e-mail: sales@so-low.com
Fax (513) 772-0570 http://www.so-low.com

ENGINEERS AND MANUFACTURERS OF ULTRA-LOW FREEZERS

SO-LOW CHEST STYLE FREEZER TO -85ºC

MODEL C85-5

5 Cubic Ft. (142 liters) Chest – Temperature Range: -40°C to -85°C

Top Opening

Specifications:

* Capacity	5 cubic ft. / 142 liters
* Temperature Range	-40°C to -85°C
* Dimensions	
* Exterior W x D x H	40.5” x 31” x 43.75” 102 x 81 x 111 (cm)
* Interior W x D x H	30” x 18” x 16” 76 x 46 x 40 (cm)



TEMPERATURE CONTROL
Microprocessor control displays set point and chamber temperature.

ALARM SYSTEM WITH RELAY
The battery operated alarm system will emit an audible and visual signal when there is a mechanical or electrical failure. The alarm has an over and under temperature setting, alarm silencing switch, and battery test switch. Also provided is a relay for remote alarm hook-up.

REFRIGERATION SYSTEM
A So-Low cascade system with two hermetic compressors. CFC & HCFC free refrigerants

CONSTRUCTION
Chamber is 14-ga. Zinc coated galvanized steel. Exterior is 16-ga. steel. Power coated cool gray.

VOLTAGE
115 volts 60 hertz, 1 phase.
15 AMP dedicated circuit required.
ETL electrical approval.

TECHNICAL SUPPORT
Supplied by Nation-Wide-Network of service companies.

Specifications subject to change without notice